

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
5 August 2004 (05.08.2004)

PCT

(10) International Publication Number  
**WO 2004/064492 A1**

(51) International Patent Classification<sup>7</sup>: **A01D 34/416**

(21) International Application Number:

PCT/IB2004/000770

(22) International Filing Date: 23 January 2004 (23.01.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
03/00712 23 January 2003 (23.01.2003) FR

(71) Applicant (for all designated States except US): **SPEED FRANCE** [FR/FR]; Parc d'activité d'Arnas, 53, rue de Chavanne, F-69400 Arnas (FR).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **LEGRAND, Emmanuel** [FR/FR]; Le Bourg, F-01480 Villeneuve (FR).


(74) Agents: **MARTIN, Jean-Jacques et al.**; Cabinet Regimbeau, 20, rue de Chazelles, F-75847 Paris Cedex 17 (FR).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK,

[Continued on next page]

(54) Title: A CUTTING HEAD FOR A BRUSH CUTTER, EDGE TRIMMER OR SIMILAR



(57) Abstract: A cutting head for a brush cutter, edge trimmer or similar, the head comprises a passageway (112) for a cutter string (300) and at least one curved surface (120) for supporting the string, the surface extending between an exit region (115) for said string from said passageway and a peripheral region of the head. According to the invention, the passageway extends (A) in a manner that is offset from an axis of rotation (C) of the head so as to present an inside edge constituted by its edge closest to said axis of rotation, said inner edge corresponding to a trailing edge of the string while the head is rotating, and the curved portion extends from said inner edge. This serves to reduce the radius of curvature of the curved portion without needing to increase the diameter of the head.